

# prisma VENT AQUA

## Active humidification in non-invasive ventilation.

With the new prisma VENT AQUA, Löwenstein offers the ideal **respiratory humidifier** for Non-Invasive Ventilation (NIV). The system can be used together with different ventilators to deliver ideally conditioned respiratory gas to mechanically ventilated patients.

The humidifier is equipped with three humidification levels, a status display and an intuitive alarm management system.

The **three operating modes** give user and patient a broad usage spectrum for the conditioning of respiratory gas during NIV therapy, ranging from continuous positive pressure (e.g., sleep apnea treatment at home) to intense respiratory support in the hospital.

A special feature is the integrated sensor with **Ambient Temperature Sensing (ATS) technology**, which takes ambient temperature into account and adjusts to the varied environmental conditions at home and in the hospital. The automatic adaptation makes therapy more comfortable for the patient.

prisma VENT AQUA can be used with a heated or unheated breathing tube system, mask and nasal cannula.

### Powerful

prisma VENT AQUA has three operating modes:

- NHW (Non Heated Wire) – Operation without heated wire and temperature sensor
- HWC (Heated Wire Calculated) – Operation with heated wire but without temperature sensor
- HWT (Heated Wire Temperature) – Operation with heated wire and temperature sensor

When it is switched on, prisma VENT AQUA automatically detects the connected accessories and selects the corresponding operating mode.

### Safe and efficient

- Intuitive alarm management
- Can be used with different non-invasive ventilators

### User-friendly

- Simple use with two symbol keys
- Automatic function detection upon start-up
- Three humidification levels
- Humidification status display





# prisma VENT AQUA

## Humidifier and Accessories

<b>prisma VENT AQUA</b> Respiratory humidifier (including temperature sensor, hot wire distributor cable, power cord)	100506	<b>Reusable humidifier</b> C500R, 500ml	550.183	<b>High-Flow leakage circuit</b> heated (i), auto-fill chamber, passive valve, connection for HFT nasal cannula (150 cm + 60 cm, 22 mm Ø)	271705
<b>prisma VENT AQUA basic</b> Respiratory humidifier (basic device)	100501	<b>Auto-fill humidification chamber</b> C200AF	ac500.300e	<b>Single patient circuit valve system</b> heated (i), with auto-fill chamber for prisma VENT AQUA or AIRcon (150 cm + 60 cm, 22 mm Ø)	271708
<b>Heated wire adapter</b>	100942			<b>Single patient circuit valve system</b> heated (i), with auto-fill chamber for prisma VENT AQUA or AIRcon (150 cm + 60 cm, 15 mm Ø)	271707
<b>Temperature sensor, 160 cm</b>	100910				
<b>Temperature sensor, 180 cm</b>	100909				

## Technical Data

Classification as per IEC 60601	Device (type of electric shock protection) Class II Application parts (degree of electric shock protection) Type BF - Heated / unheated breathing tube - Temperature sensor Housing (protection from damaging ingress of water and solids IP22 <sup>(1)</sup> )	Sound pressure level of alarms	max. 65 dB
Dimensions W x H x D	15 x 14.2 x 20 cm	Max. water volume	200 ml
Weight	about 2.3 kg / about 2.5 kg with accessories included in delivery	Gas leakage	at max. operating pressure: < 10 ml/min <sup>(3)</sup> at 60 mbar: < 5 ml/min <sup>(3)</sup>
Operating voltage	220 V – 240 V	Pressure decrease	< 0.02 (mbar*min) / liters <sup>(3)</sup>
Power frequency	50 Hz / 60 Hz	Internal compliance	Minimum 1.0 ml/mbar <sup>(3)</sup> Maximum 2.0 ml/mbar <sup>(3)</sup>
Power consumption	max. 260 VA	Temperature	· in operation: +18°C – +28°C · for storage and transport: -25°C – +70°C
Heating plate	170 W	Gas inlet temperature	+18°C – +28°C <sup>(4)</sup>
Inspiratory tube eating	22 V, 30 W	Humidity	· in operation: 15 – 93% not condensed · for storage and transport: 15 – 93% not condensed
Warm-up time	max. 30 min, usually 10 – 15 min	Atmospheric pressure	· in operation: 700 hPa – 1060 hPa · for storage and transport: 500 hPa – 1200 hPa The level of humidification decreases when the therapy device delivers respiratory gas of a higher temperature.
Flow rate	5 – 60 l/min	Temperature sensor	9.5°C – 50°C (close to patient) 5°C – 80°C (humidifying chamber)
Humidifying system dosage	> 10 mg/l from 5 – 60 l/min	Application parts	- Heated / unheated breathing tube - Temperature sensor
Maximum operating pressure	200 mbar <sup>(2)</sup>		
Continuous noise level	< 50 dB (1m)		

- (1) Protected against solid objects > 12.5 mm (such as a finger) and against direct sprays of water when housing is tilted 15° from the vertical.  
 (2) As long as the Instructions for Use for the humidifying chamber do not stipulate lower maximum pressures.  
 (3) Depending on the humidifying chamber and the breathing tube system used.  
 The information refers to the heated 22-mm system with humidifying chamber 271579.  
 (4) The maximum gas outlet temperature of the therapy device is at 23°C, room temperature is 32°C.

Learn more about prisma VENT AQUA

Please refer to the current price list.

CE 0197



WILAMED  
Aurachhöhe 5 – 7,  
91126 Kammerstein, Germany

Löwenstein Medical  
Arzbacher Straße 80  
56130 Bad Ems, Germany  
T. +49 2603 9600-0  
F. +49 2603 9600-50  
info@loewensteinmedical.com



loewensteinmedical.com

